



HD 3 is a very competent OB unit, manned with equally competent people. The unit is equipped to handle any production of sports, entertainment and other events. HD 3 comes with one big and one small production room and a separate VT area, making it a complete broadcasting facility. The track record includes the Beijing Olympics, productions for all Scandinavian TV channels and a large number of international ones – as well as numerous opera and theatre productions.

www.mediatecgroup.com

Sweden +46 10 454 03 00 | Denmark +45 278 956 21 | Norway +47 23 68 98 00
Switzerland +41 71 388 00 55 | UK +44 1794 51 67 87 | Germany +49 7031 418 06 0

Product sheet

HD-3

30 cam High Definition OB Truck

Vehicle

Trailer
Lenght / Width / Height:
16,5 m / 2,55 (5,4 m extended) / 4,00 m
Power 2 x 63 A or 1 x 125A 3-phase 400 VAC

Cameras 1080i

Grass Valley LDK-8000 HD Worldcam up to 1080P Fiber.
Grass Valley LDK-8300 HD (3 and 2 times speed) up to 1080P Fiber.

Production 1 (5.1 monitoring)

Vision Switcher:
Grass Valley Kayenne (96 inputs)
4,5 M/E, 48 o/p 4< CF, 4 Key M/E (Chroma key)
Macros, Snapshot, 6 ch. Ram recorder
Multiple Channel Integrated DVE Kayak 200
2 ME panel in second production.
2 pc. Vutrix 23" PGM/PVW 1080p

Production 2

Kayak 200 2 ME panel in second production
6 pc. Vutrix quad multiview 23" (24 previews)
6 pc. Vutrix 6" LCD

Vision

6 pc. Sony 14" CRT
30 pc. Vutrix 6" LCD pvw
2 pc. ForA Color corrector

Video Routing - Multiview/Converters

Grass Valley Trinx 320 x 512 HD (3G)
Grass Valley 28 pc. HD/SDI Cross converter with synchr./Ratio
12 Evertz VIP Multiview system (1920x1080)
UMD, Audio meter Etc.

Slomo/Vtr

7 pc. Vutrix quad multiview 23"
14 pc. Vutrix 6" LCD

Graphics System

On Request

Audio Mixer/Router

LAWO mc66 - Router
81.92 x 81.92
128 mic/Line i/p + 96 x 160 Line in/out
228 x 240 AES in/out
69 Emb/deembedders
Fiber to Stageboxes and other Routers + ATM/MADI
Ports
Audio Follow Video
2 Dolby-E Enc/Dec
Rev./Eff. T.C. Electronics 3000, 4000, 6000, Eventide
8000

Audio Cntrl Surface 1 (Mix pos. 1)

40+8 Faders, 360 DSP ch., Genelec 5:1 Monitoring

Audio Cntrl Surface 2 (Mix pos. 2)

Zirkon: 12 Faders, 44 DSP, 48 sumbuses

Intercom

RIEDEL 128 x 128 (Expandable), 32 Int. Panels,
24 Ext. -
32 Ext. 4-w, 2-w PL Lines, RTS Stereo Beltpacks
RT - 4 ch. Duplex
Integrated with Audio Router
Fiberport to external matrix

Router/Data Cntrl System

Broadcast Solutions: 35 LCD cntrl panels, UMD:s -
Gpi/Tally Mtx, unlimited serial GPI/Tally Cntr
Hardware/software redundancy

Vtr/Hard disc

Sony HD Cam SR / HD Cam / Digi Beta / DVD
EVS HD XT2, 6 ch. MultiCam, SLSM & Sportnet
X-file, X-store, IP-Director
Grass Valley K2 serve